

# NOCTIS MAX CCT

SLI029085CCT\_PW

NOCTIS MAX CCT FLOODLIGHT 100W CCT 230V IP65 294x223x28mm GREY 5Y WARRANTY



|                 |                        |                           |                             |
|-----------------|------------------------|---------------------------|-----------------------------|
| Power           | <b>100 W</b>           | Voltage                   | <b>230 V</b>                |
| Luminous flux*  | <b>10000 lm (120°)</b> | Colour temperature        | <b>3000 / 4000 / 6000 K</b> |
| Colour of light | <b>CCT</b>             | Beam angle                | <b>85 °</b>                 |
| IK              | <b>08</b>              | Degree of protection (IP) | <b>IP65</b>                 |

## Technical data

|                              |  |
|------------------------------|--|
| Code                         | SLI029085CCT_PW  |
| Power                        | 100 W  |
| Nominal current              | 405 mA   |
| Voltage                      | 230 V  |
| Energy consumption           | 100 kWh/1000h  |
| Frequency                    | 50HZ Hz  |
| Protection class             | I  |
| Power factor                 | 0.990000   |
| Useful luminous flux*        | 10000 lm (120°)  |
| Luminous flux                | 10000 lm (360°)  |
| Lamp efficacy                | 100 lm/W   |
| Luminous intensity           | 6500 cd  |
| Colour temperature           | 3000 / 4000 / 6000 K                                   |
| Colour of light              | CCT  |
| Beam angle                   | 85 °   |
| RA                           | 80   |
| Light source included        | Yes  |
| Uniformity of color SDCM max | 5  |
| Dimmable                     | No   |
| Working temperature range    | 20 to +40 °  |
| Warranty                     | 5 years  |
| Lifespan                     | 50000 h  |
| (On/Off)                     | 25000  |
| Housing material             | aluminum   |
| IK                           | 08   |
| Degree of protection (IP)    | IP65   |
| Colour                       | Szary  |
| Dimension (AxBxC)            | 294x223x28 mm  |
| For use                      | Outside  |
| Assembly method              | On the ceiling   |
| Application                  | EXT  |
| Other                        | Light color change function<br>3000K / 4000K / 6000K , |

## Logistics data

|                       |          |
|-----------------------|----------|
| Bulk packaging        | 10 pcs.  |
| Quantity per pallet   | 300 pcs. |
| Gross weight (1 pcs.) | 0.94 kg  |

\*applies to the LED source used

## Related documents



 User manual



 Declaration of Conformity